

3035T5



Sicherheitsschrank Typ 30 - EN 14470-1 - Hoch 2 Türen - 5 Schubladen

ÜBEREINSTIMMUNG

EN 14470-1, FM 6050

ADVANTAGES

- 30-minute fire resistant and made in France
- Storage of flammables

SONDERN AUCH...

- Thermo-expanding seals of the doors
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Adjustable leveling feet for enhance stability
- Geeignet für den Transport mit Hubwagen
- Tested and approved according to FM 6050
- Drawers with automatic closure in case of a fire



TECHNISCHE DATEN

Referenz
Übereinstimmung
Baustoffe der Sicherheitsschränke

3035T5
EN 14470-1, FM 6050
Melamine

Türfarbe
Anzahl der Türen
Art der Türen
Scharniere

hellgrau RAL 7035
2
flügeltüren
rechts und links

Verriegelung der Türen
Versandabmessungen HxBxT (mm)
Belüftung

Durchmesser der Öffnungen (mm)
Anzahl der Abteile / Fächer
Auffangwanne
Codenummer

selbstschließend
1400 x 1200 x 800
zuluftöffnung und abluftöffnung
auf dem dach
100
1
1
94036000

COMPLEMENTARY ACCESSORIES - VENTILATION AND FILTRATION BOXES

- Lüftungskasten (Réf : CDV-A)
- Filteraufsätze (ohne Filter) - NF X 15-211 (Réf : H50C)
- Anschlusse für Filteraufsätze (Réf : KRC)

Referenz	Äußere Abmessungen HxBxT (mm)	Innere Abmessungen HxBxT (mm)	Lagerkapazität (L)	Auffangwanne	Regale	Tragfähigkeit	Gewicht (Kg)
3035T5	1980 x 1115 x 550	1581 x 1001 x 419	250	1	0	50	270.00