

Sicherheitsschrank Typ 90 - EN 14470-1 - Untertisch 1 Schiebetür

ÜBEREINSTIMMUNG

EN 14470-1, EN 1363-1

ADVANTAGES

- 105-minute fire resistant and made in France
- Storage of flammables

SONDERN AUCH...

- Thermo-expanding seals of the doors
- Locking system
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Fixation for earthing
- 90-minute fire resistant according to EN 14470-1, and tested until 105 minute
- Tested and approved according to FM 6050
- Tested and approved with ISO 834 fire heating curve by an European laboratory



TECHNISCHE DATEN

Referenz	791T	Versandabmessungen HxBxT (mm)	900 x 1200 x 800
Übereinstimmung	EN 14470-1, EN 1363-1	Belüftung	zuluftöffnung und abluftöffnung an der Rückseite
Baustoffe der Sicherheitsschränke	Stahl 12/10	Durchmesser der Öffnungen (mm)	100
Türfarbe	weiß RAL 9010	Anzahl der Abteile / Fächer	1
Anzahl der Türen	1	Auffangwanne	1
Art der Türen	Schiebetüren	Codenummer	94032080
Verriegelung der Türen	selbstschließend		

COMPLEMENTARY ACCESSORIES - VENTILATION AND FILTRATION BOXES

- Lüftungskasten (Réf : CDV-A)
- Anschlüsse für Filteraufsätze (Réf : KRC)
- Filteraufsätze (ohne Filter) - NF X 15-211 (Réf : H40+)

OPTIONS

- Gitterrost für Sicherheitsschranke 761T - 791T (Réf : C1T)

Referenz	Äußere Abmessungen HxBxT (mm)	Innere Abmessungen HxBxT (mm)	Lagerkapazität (L)	Auffangwanne	Regale	Tragfähigkeit	Gewicht (Kg)
791T	670 x 635 x 615	460 x 490 x 380	30	1	0	0	155.00