

B22S



FM Sicherheitsschrank für korrosive Produkte - Hoch 1 Tür

ÜBEREINSTIMMUNG

FM - OSHA - NFPA

ADVANTAGES

- NFPA and OSHA compliant
- Konform FM
- Storage of corrosives

SONDERN AUCH...

- Fixation for earthing
- Continious piano hinges
- Containment sump integrated with HDPE protection
- NFPA, OSHA and FM compliant
- Rugged construction with double wall
- Adjustable shelves in height with HDPE protection
- Integrated door handle
- Self-closing doors



TECHNISCHE DATEN

Referenz	B22S	Verriegelung der Türen	selbstschließend
Übereinstimmung	FM - OSHA - NFPA	Versandabmessungen HxBxT (mm)	1850 x 1200 x 800
Baustoffe der Sicherheitsschränke	Stahl	Belüftung	lüftungsöffnungen oben und unten
Türfarbe	blau	Durchmesser der Öffnungen (mm)	50
Anzahl der Türen	1	Anzahl der Abteile / Fächer	1
Art der Türen	flügeltüren	Codenummer	2147483647
Scharniere	rechts		

COMPLEMENTARY ACCESSORIES - VENTILATION AND FILTRATION BOXES

- Filteraufsätze mit filter für organische und korrosive Dämpfe (Réf : CDF-ACORG)
- Filteraufsätze aus PVC mit filter für organische und korrosive Dämpfe (Réf :)
- Lüftungskasten (Réf : CDV-A)
- Filteraufsätze (ohne Filter) - NF X 15-211 (Réf : H50C)
- Anschlüsse für Filteraufsätze (Réf : KRC)

OPTIONS

- Regal für Sicherheitsschranke B22M - B22S (Réf : ESP22)

Referenz	Äußere Abmessungen HxBxT (mm)	Innere Abmessungen HxBxT (mm)	Lagerkapazität (L)	Auffangwanne	Regale	Tragfähigkeit	Gewicht (Kg)
B22S	1651 x 591 x 457	1560 x 500 x 390	86		3	159	88.00