794+LI

Security cabinet 90 min lithium batteries - Tall cabinet 1 door to equip

COMPLIANCE

ADVANTAGES

- 105-minute fire resistant and made in France
- Storage of flammables
- Storage of lithium-ion batteries

BUT ALSO...

- Locking system
- Thermo-expanding seals of the doors
- Holes for the connection to the ventilation
- Proven resistance of 105 minutes
- Reduce the risk of fire and explosion

TECHNICAL FEATURES

Model	**794+LI**	Shipping dimensions HxWxD (mm)	**2150 x 1200 x 800**
Cabinet materials	**Sheet steel 12/10th and inner body built in melami**	Ventilation	**Both inlet and outlet on the top of the cabinet**
Doors color	**white RAL 9010**	Openings diameter (mm)	**100**
Number of doors	**1**	Connecting sleeve	**1**
Doors type	**swing door**	Number of compartments	**1**
Hinges	**right**	HS Code	**94032080**
Door closure	**automatic closing**		

ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Containment sump for 1- door cabinets Types 30, 60 & 90 (Réf : B148)
- Perforated cover plate for 1-door or multirisk safety cabinets Types 30, 60 & 90 (Réf : C148)
- Filtration box with activated carbon filter for organic and corrosive vapors (Réf : CDF-ACORG)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Recirculating air box Labopur - NF X 15-211 (Réf : H50C)
- Connecting kit (Réf : KRC)
- Perforated shelf for 1-door safety cabinet (Réf : E48LI)
- 79°C Special Lithium Battery Automatic Fire Extinguisher (Réf : EX100LI)
- Rack of 9 electrical outlets (Réf : PRISELI)
- Visual & audible alarm + control box + smoke detector + fire extinguisher EX200Li + cable duct (Réf : VIG290)
- Rack of 9 electric outlets type F (Germany) (Réf : PRISELIF)
- Rack of 8 electrical outlets type J (Switzerland) (Réf : PRISELICH)
- Rack of 7 G-type electrical outlets (UK) (Réf : PRISELIUK)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
794+LI	1950 x 635 x 620	1620 x 490 x 410	0		0	80	287.00

138 avenue Henri BARBUSSE 92140 Clamart (France)
Tél. 01 46 45 80 00 - Fax : 01 46 45 85 98
www.trionyx.fr - trionyx[at]trionyx.fr