

3035T6



2- door tall safety cabinet Type 30 with 6 sliding drawers

COMPLIANCE

EN 14470-1 FM 6050

ADVANTAGES

- 30-minute fire resistant and made in France
- EN 14470-1 and FM 6050 compliant
- Storage of flammables

BUT ALSO...

- Thermo-expanding seals of the doors
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Adjustable leveling feet for enhance stability
- Pedestal area under-driveable by a forklift by removing panel
- Tested and approved according to FM 6050
- Drawers with automatic closure in case of a fire



TECHNICAL FEATURES

Model	3035T6	Door closure	self-closing
Compliance	EN 14470-1 FM 6050	Shipping dimensions HxWxD (mm)	2180 x 1200 x 800
Cabinet materials	Melamine wood structure	Ventilation	Both inlet and outlet on the top of the cabinet
Doors color	light grey RAL 7035	Openings diameter (mm)	100
Number of doors	2	Number of compartments	1
Doors type	swing doors	Containment sump	6
Hinges	right & left	HS Code	94036000

ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Ventilation box for a connection to the outside (Réf : CDV-A)
- Recirculating air box Labopur - NF X 15-211 (Réf : H50C)
- Connecting kit (Réf : KRC)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
3035T6	1980 x 1115 x 550	1580 x 1050 x 420	250	6	0	50	287.00