

3031E



1- door underbench safety cabinet Type 30

COMPLIANCE

EN 14470-1, FM 6050

ADVANTAGES

- 30-minute fire resistant and made in France
- EN 14470-1 and FM 6050 compliant
- Storage of flammables

BUT ALSO...

- Thermo-expanding seals of the doors
- Adjustable leveling feet for enhance stability
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Tested and approved according to FM 6050
- Pedestal area under-driveable by a forklift by removing panel



TECHNICAL FEATURES

Model	3031E	Shipping dimensions HxWxD (mm)	835 x 1200 x 800
Compliance	EN 14470-1, FM 6050	Ventilation	Both inlet and outlet on the back wall of the cabinet
Cabinet materials	Melamine wood structure	Openings diameter (mm)	100
Doors color	light grey RAL 7035	Number of compartments	1
Number of doors	1	Containment sump	1
Doors type	swing doors	Grating	1
Hinges	right	HS Code	94036000
Door closure	self-closing		

ADDITIONAL ACCESSORIES RECOMMENDED – FILTRATION OR VENTILATION BOXES

- Ventilation box for a connection to the outside (Réf : CDV-A)
- Recirculating air box Labopur - NF X 15-211 (Réf : H50C)
- Connecting kit (Réf : KRC)
- Vertical recycling air box (delivered without filter) (Réf : H40+)

OPTIONS

- Containment sump for 1- door cabinets Types 30, 60 & 90 (Réf : B148)
- Perforated cover plate for 1-door or multirisk safety cabinets Types 30, 60 & 90 (Réf : C148)
- Retention shelf for 1-door or multirisk safety cabinets Types 30, 60 & 90 (Réf : E48)
- Containment sump in PVC for 1-door or multirisk safety cabinets Types 30, 60 & 90 (Réf : SB148)
- Protection shelf in PVC for 1-door or multirisk safety cabinets Types 30, 60 & 90 (Réf : SE148)
- Sliding drawer for 1-door or multirisk safety cabinets Types 30, 60 & 90 (Réf : T148)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
3031E	635 x 605 x 630	366 x 495 x 420	30	1	0	30	64.00