

795+T5



2- door tall safety cabinet Type 90 with 5 sliding drawers

COMPLIANCE

EN 14470-1

ADVANTAGES

- 105-minute fire resistant and made in France
- EN 14470-1 and EN 1363-1 compliant
- Storage of flammables

.

BUT ALSO...

- Adjustable shelves in height
- Locking system
- Thermo-expanding seals of the doors
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Fixation for earthing
- 90-minute fire resistant according to EN 14470-1, and tested until 105 minute
- Tested and approved according to FM 6050
- Tested and approved with ISO 834 fire heating curve by an European laboratory



TECHNICAL FEATURES

Model	795+T5	Door closure	self-closing
Compliance	EN 14470-1	Shipping dimensions HxWxD (mm)	2150 x 1200 x 800
Cabinet materials	12/10th epoxy painted steel structure	Ventilation	Both inlet and outlet on the top of the cabinet
Doors color	white RAL 9010	Openings diameter (mm)	100
Number of doors	2	Number of compartments	1
Doors type	swing doors	Containment sump	5
Hinges	right & left	HS Code	94032080

ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Ventilation box for a connection to the outside (Réf : CDV-A)
- Recirculating air box Labopur - NF X 15-211 (Réf : H50C)
- Connecting kit (Réf : KRC)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
795+T5	1950 x 1137 x 620	1620 x 1000 x 410	250	5	0	50	495.00