

1- sliding door underbench safety cabinet Type 90

COMPLIANCE

EN 14470-1, EN 1363-1

ADVANTAGES

- 105-minute fire resistant and made in France
- EN 14470-1 and FM 6050 compliant
- Storage of flammables

BUT ALSO...

- Thermo-expanding seals of the doors
- Locking system
- Holes for the connection to the ventilation
- Normalized labelling provided with the equipment
- Fixation for earthing
- 90-minute fire resistant according to EN 14470-1, and tested until 105 minute
- Tested and approved according to FM 6050
- Tested and approved with ISO 834 fire heating curve by an European laboratory



TECHNICAL FEATURES

Model	792T	Door closure	self-closing
Compliance	EN 14470-1, EN 1363-1	Shipping dimensions HxWxD (mm)	900 x 1200 x 800
Cabinet materials	12/10th epoxy painted steel structure	Ventilation	Both inlet and outlet on the back wall of the cabinet
Doors color	white RAL 9010	Openings diameter (mm)	100
Number of doors	2	Number of compartments	1
Doors type	sliding doors	Containment sump	1
Hinges	right & left	HS Code	94032080

ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Ventilation box for a connection to the outside (Réf : CDV-A)
- Connecting kit (Réf : KRC)
- Vertical recycling air box (delivered without filter) (Réf : H40+)

OPTIONS

- Perforated cover plate for cabinets 762T - 792T (Réf : C2T)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
792T	670 x 1135 x 615	460 x 1000 x 380	60	1	0	0	240.00