793+NLI35

Storage and utility cupboard – 105 mm – counter, 2 doors – P3500T1

COMPLIANCE

ADVANTAGES

- Connected alarm | smoke detector
- Fire extinguisher
- Manual security check
- French manufacturing - CSR
- The most powerful battery can reach up to 3500 Wh
- Open-door alarm
- Flame protection system
- Dry contact
- Tested 105 min - from outside to inside in accordance with standard EN14470-1
- Circuit breaker
- Ballistic protection system
- Storage of lithium-ion batteries
- Inside to outside fire-stop construction EI180

BUT ALSO...

- Locking system
- Thermo-expanding seals of the doors
- Holes for the connection to the ventilation
- Reduce the risk of fire and explosion



TECHNICAL FEATURES

Model	**793+NLI35**	Ventilation	**Both inlet and outlet on the top of the cabinet**
Doors color	**Black RAL 9005**	Openings diameter (mm)	**100**
Number of doors	**2**	Connecting sleeve	**1**
Doors type	**swing doors**	Number of compartments	**1**
Hinges	**left and right**	HS Code	**94032080**

ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Rack of 9 electrical outlets (Réf : PRISELI)
- Rack of 6 electrical outlets equipped with a thermal-magnetic circuit breaker (Réf : PRISELICC)
- Rack of 7 G-type electrical outlets (UK) (Réf : PRISELIUK)
- Rack of 8 electrical outlets type J (Switzerland) (Réf : PRISELICH)
- Rack of 8 electric outlets type F (Germany) (Réf : PRISELIF)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
793+NLI35	1220 x 1137 x 670	1620 x 1000 x 410	0		2	0	302.00

TRIONYX DEPUIS 1971

138 avenue Henri BARBUSSE 92140 Clamart (France)
Tél. 01 46 45 80 00 - Fax : 01 46 45 85 98
www.trionyx.fr - trionyx[at]trionyx.fr