

2- door tall safety cabinet Type 90 - 4 compartments

COMPLIANCE

EN 14470-1, EN 1363-1

ADVANTAGES

- 105-minute fire resistant and made in France
- EN 14470-1 and EN 1363-1 compliant
- Storage of flammables, corrosives and toxics

BUT ALSO...

- 90-minute fire resistant according to EN 14470-1, and tested until 105 minute
- Built in cellular PVC for acids-bases-toxics compartments
- Holes for the connection to the ventilation
- Fixation for earthing (for flammable part)
- Self-closing door if the temperature rises to 47°C



TECHNICAL FEATURES

Model	MR9+	Door closure	manual & self-closing
Compliance	EN 14470-1, EN 1363-1	Shipping dimensions HxWxD (mm)	2400 x 1300 x 800
Cabinet materials	Corrosive part in cellular PVC, Flammable part in white RAL 9010	Ventilation	Both inlet and outlet
Doors color	4	Openings diameter (mm)	100
Number of doors	swing doors	Number of compartments	4
Doors type	right & left	Containment sump	1
Hinges		HS Code	94032080

ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

- Filtration box with activated carbon filter for organic and corrosive vapors (Réf : CDF-ACORG)
- Filtration box built in PVC with activated carbon filter for organic and corrosive vapors (Réf :)
- Ventilation box for a connection to the outside (Réf : CDV-A)
- Recirculating air box Labopur - NF X 15-211 (Réf : H50C)
- Connecting kit (Réf : KRC)

OPTIONS

- Containment sump built in polypropylene (Réf : E8A2)
- Containment sump for 1- door cabinets Types 30, 60 & 90 (Réf : B148)
- Perforated cover plate for 1-door or multirisk safety cabinets Types 30, 60 & 90 (Réf : C148)
- Retention shelf for 1-door or multirisk safety cabinets Types 30, 60 & 90 (Réf : E48)
- Sliding drawer for 1-door or multirisk safety cabinets Types 30, 60 & 90 (Réf : T148)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
MR9+	2205 x 1270 x 615		210	1	3	30	400.00