ABST120



COMPLIANCE

ADVANTAGES

Complies with risk prevention and safety recommendations
 Designed to be placed under-bench

BUT ALSO

• Especially designed to • Equipment allowing • C settle under the bench space saving

> Normalized labelling provided with the equipment

- Holes for the connection to the ventilation
- Possibility to add swivel castors, for an easy movement of the cabinet



flammables, corrosives and toxics

Storage of

system

Risques & Sécurité

TECHNICAL FEATURES

Model Cabinet materials

Doors color

Number of doors Doors type Hinges Door closure ABST120 15/10th epoxy painted steel structure blue RAL 5015, white RAL 9010, yellow RAL 1023 & w 4 swing doors right & left self-closing Shipping dimensions HxWxD (mm) Ventilation Openings diameter (mm)

```
Number of compartments
Containment sump
HS Code
```

870 x 1200 x 800 Both inlet and outlet

100

3 4

94032080

ADDITIONAL ACCESSORIES RECOMMENDED - FILTRATION OR VENTILATION BOXES

 Ventilation box for a connection to the outside (Réf : CDV-A) Connecting kit (Réf : KRC) Vertical recycling air box (delivered without filter) (Réf : H40+)

OPTIONS

 4 swivel castors 2 with locking (Réf : 4ROU)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Storage capacity (L)	Containment sump	Shelves	Load capacity	Weight (kg)
ABST120	670 x 2200 x 500	(4x) 650 x 530 x 470	120	4	4	50	120.00



138 avenue Henri BARBUSSE 92140 Clamart (France) Tél. 01 46 45 80 00 - Fax : 01 46 45 85 98 www.trionyx.fr - trionyx[at]trionyx.fr