

# Combination shower eyewasher for indoor use

## COMPLIANCE

EN 15154-1, EN 15154-2, NF X 15-221

## ADVANTAGES

- ISO 3864 compliant
- EN 15154-1 and EN 15154-2 compliant
- First-aid in case of chemical projection

### BUT ALSO...

- EN 15154-1 and EN 15154-2 compliant
- Allows to rinse itself the body in case of chemical projection
- Delivered with the first-aid labelling
- Anti-dust caps for dusty environment
- Compliant to the article R. 4224-14 of the Labour Code



## TECHNICAL FEATURES

Model	<b>DLP62</b>	Bowl	<b>stainless steel</b>
Compliance	<b>EN 15154-1, EN 15154-2, NF X 15-221</b>	Shower head	<b>stainless steel</b>
Shipping dimensions HxWxD (mm)	<b>350 x 250 x 860</b>	Pipe	<b>stainless steel</b>
Use	<b>internal use</b>	Water inlet	<b>F1"</b>
Setting	<b>handle and foot operating</b>	Water outlet	<b>F1 1 / 4"</b>
	<b>mounted on feet</b>	HS Code	<b>73242921</b>

## OPTIONS

- Thermostatic mixing valve for safety shower and combination unit (Réf: MTD)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Eye-washer flow (L/min)	Shower flow (L/min)	Weight (kg)
DLP62	2200 x 640		11	75	22.00