DLV52

Combination shower eyewasher for indoor use

COMPLIANCE

EN 15154-1, EN 15154-2, NF X 15-221

ADVANTAGES

- ISO 3864 compliant
- EN 15154-1 and EN 15154-2 compliant
- First-aid in case of chemical projection

BUT ALSO...

- EN 15154-1 and EN 15154-2 compliant
- Anti-dust caps for dusty environment
- Compliant to the article R. 4224-14 of the Labour Code
- Delivered with the first-aid labelling
- Allows to rinse itself the body in case of chemical projection



TECHNICAL FEATURES

Model	**DLV52**	Bowl	**stainless steel**
Compliance	**EN 15154-1, EN 15154-2, NF X 15-221**	Shower head	**stainless steel**
Shipping dimensions HxWxD (mm)	**350 x 260 x 860**	Pipe	**stainless steel**
Use	**internal use**	Water inlet	**F1''**
	handle and foot operating	Water outlet	**F1 1 / 4''**
Setting	**mounted on feet**	HS Code	**73242921**

OPTIONS

- Thermostatic mixing valve for safety shower and combination unit (Réf : MTD)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Eye-washer flow (L/min)	Shower flow (L/min)	Weight (kg)
DLV52	2200 x 640		11	75	19.00

TRIONYX DEPUIS 1971

138 avenue Henri BARBUSSE 92140 Clamart (France)
Tél. 01 46 45 80 00 - Fax : 01 46 45 85 98
www.trionyx.fr - trionyx[at]trionyx.fr