DS23

Safety shower – wall mounted for indoor use

COMPLIANCE

EN 15154-1, NF X 15-221

ADVANTAGES

- ISO 3864 compliant
- EN 15154-1 and NF X 15-221 compliant
- First-aid in case of chemical projection

BUT ALSO...

- EN 15154-1 compliant
- Delivered with the first-aid labelling
- Compliant to the article R. 4224-14 of the Labour Code



TECHNICAL FEATURES

Model	**DS23**	Setting	**wall mounted**
Compliance	**EN 15154-1, NF X 15-221**	Shower head	**Green ABS RAL 6029**
Shipping dimensions HxWxD (mm)	**330 x 180 x 800**	Pipe	**galvanised steel + green epoxy painted RAL 6029**
Use	**internal use** **handle operating**	Water inlet	**F 1''**
		HS Code	**73242921**

OPTIONS

- Thermostatic mixing valve for safety shower and combination unit (Réf : MTD)

Model	External dimensions HxWxD (mm)	Internal dimensions HxWxD (mm)	Eye-washer flow (L/min)	Shower flow (L/min)	Weight (kg)
DS23			0	75	4.00

TRIONYX DEPUIS 1971

138 avenue Henri BARBUSSE 92140 Clamart (France)
Tél. 01 46 45 80 00 - Fax : 01 46 45 85 98
www.trionyx.fr - trionyx[at]trionyx.fr