

B18M



Armadio di sicurezza FM per prodotti corrosivi - 64 L - Manuale

CONFORMIDAD

FM - OSHA - NFPA

ADVANTAGES

- NFPA and OSHA compliant
- Conforme a la norma FM
- Storage of corrosives

SINO TAMBIÉN...

- Containment sump integrated with HDPE protection
- NFPA, OSHA and FM compliant
- Rugged construction with double wall
- Adjustable shelves in height with HDPE protection
- Integrated door handle



CARACTERISTICAS TECNICAS

Modelo	B18M	Cierre de las puertas	chiusura manuale
Conformidad	FM - OSHA - NFPA	Dimensiones de envío alt x anc x pro (mm)	810 x 1200 x 800
Materiales del armario	acciaio doppia parete	Ventilación	orificio di ventilazione alto e bassi, con griglia
Color de las puertas	blu	Diámetro de ventilación (mm)	50
Número de puertas	2	Número de compartimentos	1
Tipo de puertas	porte battenti	Código Aduanero	2147483647
Bisagras	cerniere a destra		

COMPLEMENTARY ACCESSORIES - VENTILATION AND FILTRATION BOXES

- Cassettone di filtrazione acciaio Filtra CORG (Réf : CDF-ACORG)
- Cassettone di filtrazione PVC cellulare (Réf :)
- Cassettone di ventilazione in acciaio (Réf : CDV-A)
- Gerla ed armadi hanno filtrazione - Ventilazione - Cassettone ha recirculation di aria senza filtro (Réf : H50C)
- Kit di raccordo per cassettone (Réf : KRC)

OPTIONS

- Mensola supplementare per armadio 64 L (Réf : ESP18)

Modelo	Dimensiones exteriores alt x anc x pro (mm)	Dimensiones interiores alt x anc x pro (mm)	Capacidad de almacenamiento (L)	Cubetas de retención	Estanterías	Carga admisible	Peso (kg)
B18M	610 x 1092 x 457	515 x 1005 x 390	64		1	159	58.00