MR6+

Armadio multirischi 60 min - EN 14470-1 - PVC cellulare

CONFORMITÀ

EN 14470-1, EN 1363-1

ADVANTAGES

- 60-minute fire resistant and made in France
-
- Storage of flammables, corrosives and toxics

MA ANCHE...

- EN 14470-1 Type 60 compliant
- Built in cellular PVC for acids-bases-toxics compartments
- Fixation for earthing (for flammable part)
- Self-closing door if the temperature rises to 47°C
- Fori di ventilazione con uscita di ventilazione Ø 100 mm per eventuale collegamento

CARATTERISTICHE TECNICHE

Modello	**MR6+**	Chiusura porta	**chiusura automatica e manuale**
Conformità	**EN 14470-1, EN 1363-1**	Dimensioni di spedizione HxWxD (mm)	**2400 x 1300 x 800**
Materiale	**melamina e acciaio 15/10 doppia parete**	Ventilazione	**entrata dell'aria laterale e uscita sul tetto**
Colore porte	**bianco RAL 9010**	Diametro di ventilazione (mm)	**100**
Numero di porte	**4**	Numero di compartimenti	**4**
Tipo porte	**porte battenti**	Vaschetta di contenimento	**1**
Cerniere	**cerniere a destra e sinistra**	Codice HS	**94032080**

COMPLEMENTARY ACCESSORIES - VENTILATION AND FILTRATION BOXES

- Cassettone di ventilazione in acciaio (Réf : CDV-A)
- Kit di raccordo per cassettone (Réf : KRC)

OPTIONS

- Etagere/bac di ritenzione supplementare per gli scompartimenti acidi, basi, tossici (Réf : E8A2)
- traghetto di ritenzione per armadio 1 porta - L 635 - P 615 mm (Réf : B148)
- Grigliati (Réf : C148)
- Mensola (Réf : E48)
- Vaschetta scorrevole per armadio 1 porta - L635 - P615 mm (Réf : T148)

Modello	Dimensioni esterne HxWxD (mm)	Dimensioni interne HxWxD (mm)	Capacità di stoccaggio (L)	Vaschetta di contenimento	Ripiani	Capacità di carico	Peso (kg)
MR6+	2205 x 1270 x 615		210	1	3	30	390.00

TRIONYX DEPUIS 1971

138 avenue Henri BARBUSSE 92140 Clamart (France)
Tél. 01 46 45 80 00 - Fax : 01 46 45 85 98
www.trionyx.fr - trionyx[at]trionyx.fr