

Vertical laminar air flow cabinet, 900 wide

CONFORMITÀ

EN 61010-1, EN 61326-1, EN 61000-6-3

ADVANTAGES

MA ANCHE...

- Low noise fan
- High intensity of light
- Smooth walls, rounded corners and no welds ; allowing easy cleaning and decontamination
- White walls for a glare-free brightness
- Easy replacement of the filters
- Electronic compartment located outside the contaminated area
- Microprocessor control system with digital display for airflow velocity
- Audible and visual alarm in case of airflow defect



CARATTERISTICHE TECNICHE

| | | | |
|-------------------------------------|---|-----------------------|-----------------|
| Modello | FLV09 | Flusso (m3/h) | 2150 |
| Conformità | EN 61010-1, EN 61326-1, EN 61000-6-3 | Voltaggio (volt) | 0.99999 |
| Dimensioni di spedizione HxWxD (mm) | 1500 x 1150 x 850 | Potenza elettrica (W) | 760 |
| Flusso d'aria (m/s) | 0,4 | Codice HS | 84146011 |
| Voltaggio (volt) | 220 | | |

PRODUITS COMPLÉMENTAIRES

- Front enclosure with UV light for FLV09 (Réf : FACFLV09)
- Support stand for FLV09 and PSM9 (Réf : TH09)
- Gas valve with solenoid valve (Réf : VANGAZ)
- Vacuum valve (Réf : VANVID)

| Modello | Dimensioni esterne HxWxD (mm) | Dimensioni interne HxWxD (mm) | Peso (kg) |
|---------|-------------------------------|-------------------------------|-----------|
| FLV09 | 1345 x 1060 x 795 | 620 x 890 x 630 | 165.00 |