H153Z+2C

Ductless fume hood 1500 mm - 3 modules - for liquid - one opening

CONFORMITÀ

NF X 15-211 Classe 1

ADVANTAGES

- CE certified
- NF X 15-211 compliant
- Storage of flammables, corrosives and toxics
- Norma EN 17242

MA ANCHE...

- Easy replacement of the active coal filter
- Low acoustic level
- Front control window to see immediately the filter
- NF X 15-211 compliant
- Delivered ready to use
- Interfaccia touchscreen FILTRALARME 5, funzionamento del sistema di ventilazione
- Holes for the cables and fluid going through
- Glass side walls



CARATTERISTICHE TECNICHE

Modello	**H153Z+2C**
Conformità	**NF X 15-211 Classe 1**
Flusso d'aria (m/s)	**0,4 - 0,6**
Voltaggio (volt)	**220-240**
Flusso (m3/h)	**170**
Aperture passaggio cavi	**4**
Anemometro	**included**
Guida alle sostanze chimiche adsorbite	**included**
Contaore	**included**
Presa di campionamento	**included**
Parete posteriore trasparente	**included**
Piano lavoro in melamina	**option**
Potenza elettrica (W))	**27**
Rumore dB (A)	**57.00**
Codice HS	**84146000**

PRODUITS COMPLÉMENTAIRES

- Filtro ha carbone attivo per vapori organici - for old fume hoods type 200, 201, 210 and 211 (Réf : ORG200)
- Filtro ha carbone attivo polivalente - for old fume hoods type 200, 201, 210 and 211 (Réf : CORG201)
- Filtro ha carbone attivo per formolo - for old fume hoods type 200, 201, 210 and 211 (Réf : FOR200)
- Filtro ha carbone attivo per vapori ammoniaca per sorbonne - for old fume hoods type 200, 201, 210 and 211 (Réf : AMM200)
- Containment sump and melamine work-top for H15 (Réf : BB15)
- Containment sump and tempered glass work-top for H15 (Réf : BV15)

OPTIONS

- Lighting for ductless fume hoods (Réf : LUMI)
- Table-cabinet for H15 (Réf : TA15)
- Trolley with adjustable shelf for H15 (Réf : TR15)
- Tubular table with wheels for model H15 (Réf : TTR15)
- Tubular table with feet for model H15 (Réf : TTF15)

Modello	Dimensioni esterne HxWxD (mm)	Dimensioni interne HxWxD (mm)	Peso (kg)
H153Z+2C	1160 x 1500 x 750	935 x 1445 x 700	54.00

TRIONYX DEPUIS 1971

138 avenue Henri BARBUSSE 92140 Clamart (France)
Tél. 01 46 45 80 00 - Fax : 01 46 45 85 98
www.trionyx.fr - trionyx[at]trionyx.fr