





Flammable

SAFETY CABINETS FOR TOXIC PRODUCTS AND MULTIRISK SAFETY CABINETS









COMPLIANCE

- · Complies with articles R.5132-66 and R. 5132-68 of the Public Health Code.
- · Complies with the recommendations of the I.N.R.S.
- · Standardized labels in accordance with ISO 3864, ISO 7010 standards, and with European Directive 92/58/EEC.

ADVANTAGES

- · Integrated electric fan.
- Large storage capacity.

PASSIVE SAFETY

- 10/10 steel construction.
- White epoxy paint RAL 9010.
- · Standardized «toxic» or «noxious» warning labels (to be specified when ordering).
- · 3 retention shelves, adjustable in height on racks.
- · Removable Containment sump at the bottom of the cabinet, height 100 mm.

ACTIVE SAFETY

- Integrated electric fan: 220-240 volts 0.1 A 18 W; 90 m3/h flow rate; IPX4 protection; 37.5 Lp dB(A) sound level (3m).
- Double hinged door with 3 points locking system and key lock.

OPTIONS

- · Additional shelf.
- PVC retention shelf.
- · Pull-out drawer.
- · Poison box, see below.

POISON CHESTS

- · Made of 10/10 steel.
- · White epoxy paint RAL 9010.
- · «Toxic» Standardized symbol in accordance with ISO 3864, ISO 7010 and NF X08.003 standards and directive 92/58/EEC.
- · Height adjustable shelves on racks: 2 for the MF1 model; 4 for the MF2 model.
- · Hinged door with key lock.
- · Possibility of wall mounting.
- · Possibility of assembling the models together.

	▲ MF2	▲ MF1		▲ MF4 + MF1				
 COMPLIANCE Complies with articles R.5132-66 and R. 5132-68 of the Public Health Code. Complies with the recommendations of the I.N.R.S. Standardized labels in accordance with ISO 3864, ISO 7010 standards, and with European Directive 92/58/EEC. 				OPTIONS · Additional shelf. · PVC retention shelf. · Pull-out drawer. · Poison box, see below.				
• Intege • Large • PASS • 10/10 • White • Stand when • 3 rete • Remo heigh • ACTI • Integer rate; I	ANTAGES rated electric fan. e storage capacity. IVE SAFETY steel construction. e poxy paint RAL 9010. lardized «toxic» or «noxious» warning la ordering). ention shelves, adjustable in height on rivable Containment sump at the bot to 100 mm. VE SAFETY rated electric fan: 220-240 volts - 0.1 A PX4 protection; 37.5 Lp dB(A) sound levile hinged door with 3 points locking systems.	acks. tom of the cabin - 18 W; 90 m3/h flo vel (3m).	Can be us or as pois Made of White ep «Toxic» S 7010 and Height a MF2 mod Hinged c Possibilit Possibilit	on boxes in 10/10 steel. oxy paint RA standardized I NF X08.003 djustable she	AL 9010. I symbol in a standards a elves on rack	accordance and directives: 2 for the	e with ISO 38 ve 92/58/EEC. e MF1 model; 4	64, ISC
P/N	Description	External dim. H x W x D (mm)	Internal dim. H x W x D (mm)	Storage capacity (L)	Containment capacity (L)	Number of shelves	Load capacity per shelf (kg)	Weight (kg)
	D. C. C. LAND	222 472 225	272 462 472				(Ng)	· •
MF1	Poison Chest 12 L	380 x 470 x 205	370 x 460 x 170	12	-	2	10	10
MF1 MF2	Poison Chest 12 L Poison box 19 L	380 x 470 x 205 580 x 470 x 205	370 x 460 x 170 570 x 460 x 170	12 19	-	2	10 10	
								10