



Fume hoods, filtering cabinets - Ventilation

Lithium-ion cabinets

Flammable cabinets

Corrosive cabinets

Toxic cabinets and Multirisk

Containment and cans

File cabinets Anti-fire equipments

Showers and first-aid equipments

MINI-HOODS WITH AIR RECIRCULATION Labopur®



1 Timer




2 Control window



3 Working opening



5 Containment sump integrated



4 Easy replacement



▲ H70 + CORG51

COMPLIANCE

- Adsorption capacity of active charcoal filters and filtration system tested and approved to NFX 15-211 - May 2009.
- Electric fan conforms to CE specifications.

ADVANTAGES

- Labopur® technology.
- Easily placed on a bench or workbench.
- Containment of vapors in the handling chamber and elimination of these vapors when they pass through the active charcoal filter.
- Ventilation system operation indicator light.
- Window for checking the presence of the filter adapted to your needs.
- High efficiency active charcoal filter specialised and treated according to the products stored, tested to standard NFX 15-211 - May 2009.
- Anti-dust filter, 92% efficiency against particles < 3 µm.
- Easy replacement of the active charcoal cell.
- Hour meter permanently indicating the total cabinet usage duration. After programming, every 60 hours, an acoustic signal indicates that the active charcoal filter should be checked for saturation.
- Built-in containment sump for the recovery of liquids in case of spillage.
- No connection or draining required, no civil engineering solution

(if used with active charcoal filter).

- Delivered ready to use (no assembly needed), simply connect to the electrical grid.
- Adjustable feet for levelling.

TECHNICAL CHARACTERISTICS

- 12/10th steel construction.
- White RAL 9010 and blue RAL 5015 epoxy paint.
- Silent electric fan: 220-240 volts - 27 W - 0.1 A - 57 dB(A) (excluding air flow) - flow rate: 170 m3/hour
- PMMA side walls and ergonomic hand passages for safe and easy handling in the enclosure.
- Hinged front panel with total opening for full access to the interior of the hood.

OPTIONS

- Active charcoal filter: The mini-hood is delivered without active charcoal filter. You must select one from the table below depending on the type of products you are handling.
- Element for use without active charcoal filter.
- Control of filter obsolescence by REAGENT TUBES: Control port on the side of the cabinet - Port for the introduction of specialised reagent tubes - Use of a manual pump - Detection of the efficiency or saturation of the active charcoal filter by reading the tubes.

We remind you that we can offer you filters for specific

P/N	Description	External dim. H x W x D (mm)	Internal dim. H x W x D (mm)	Weight (kg)
H70	Mini recirculating air hood (delivered without filter)	605 x 505 x 485	410 x 455 x 445	25
ORG50	Active charcoal filter for organic steam	70 x 390 x 390	-	8
CORG51	Multi-purpose active charcoal filter(1) for organic and corrosive vapors	70 x 390 x 390	-	9
FOR50	Active charcoal filter for Formaldehyde vapors	70 x 390 x 390	-	9
PMAF	Manual pump	-	-	0,4
TROR	10 "organic" test tubes	-	-	0,1
TRAC	10 "corrosive" test tubes	-	-	0,1
TROA	5 "organic" and 5 "corrosive" test tubes	-	-	0,1

(1) CORG multipurpose active charcoal filters can adsorb the vast majority of commonly used products: corrosive products, organic compounds or solvents.