

RANGE 790+T

EN
14470-1

EN
1363-1

FM
6050

90
APPROVED
EN14470-1

105
TESTED
EN14470-1

MADE IN
EUROPE



90 MINUTES SAFETY CABINETS EN 14470-1 & FM FOR FLAMMABLE PRODUCTS WITH ERGONOMIC RETENTION DRAWERS



▲ 791T



▲ 792T



▲ 794T+5
Self-closing fire containment drawers⁽²⁾



▲ 795T+6
Self-closing fire containment drawers⁽²⁾

PRE-EQUIPPED CABINETS

P/N	Description	Type	Number of door(s)	External dimensions H x W x D (mm)	Internal dimensions H x W x D (mm)	Weight (kg)
791T	Cabinet with 1 drawer	under-bench	1	670 x 635 x 615 ⁽¹⁾		155
792T	Cabinet with 1 drawer	under bench	1	670 x 1137 x 615 ⁽¹⁾		240
794+T4	1 door cabinet with 4 drawers	tall	1	1950 x 635 x 620 ⁽³⁾	1620 x 490 x 410	301
794+T5	1 door cabinet with 5 drawers	tall	1	1950 x 635 x 620 ⁽³⁾	1620 x 490 x 410	307
794+T6	1 door cabinet with 6 drawers	tall	1	1950 x 635 x 620 ⁽³⁾	1620 x 490 x 410	313
795+T4	2 doors cabinet with 4 drawers	tall	2	1950 x 1137 x 620 ⁽³⁾	1620 x 1000 x 410	483
795+T5	2 doors cabinet with 5 drawers	tall	2	1950 x 1137 x 620 ⁽³⁾	1620 x 1000 x 410	495
795+T6	2 doors cabinet with 6 drawers	tall	2	1950 x 1137 x 620 ⁽³⁾	1620 x 1000 x 410	507

ACCESSORIES

P/N	Description	External dimensions H x W x D (mm)	Weight (kg)
C1T	Perforated cover plate for 1 door cabinet 791T+	80 x 430 x 390	8
C2T	Perforated cover plate for 1 door cabinet 792T+	80 x 940 x 390	8
T148	Self retracting drawer for 1 door cabinet - exclusively for cabinet 794/798	80 x 420 x 380	6
T235	Self retracting drawer for 2 doors cabinet - exclusively for cabinet 793/795	80 x 930 x 380	12

(1) Depth with connecting sleeve at the rear. Depth without sleeve: 565 mm

(2) To be ordered at time of manufacture. Maximum quantity per cabinet: 6

(3) Height with connecting sleeve on top. Height without sleeve: 1900 mm