



SAFETY BOTTLES



▲ 1633R



▲ 1619R

ADVANTAGES

- No leakage when the bottle tips over.
- Lid can only be opened by finger pressure.
- Automatic closing.
- Precise dosing.
- Double opening and tight closing by spring and O-ring.
- Stopper with its «nitrile-rubber» seal.

TECHNICAL CHARACTERISTICS

- Aluminium body: Al 99,5.
- Threaded ring: Al Mg Si Pb.
- Plastic valve: PPN.
- Nitrile-rubber sealing ring.
- O-rings:
 - Either VITON (red cap),
 - Or EPDM (yellow cap).
- Spring: X5 Cr Ni Mo 4401.

P/N	O-rings	Capacity (L)	Dimensions H x Ø (mm)	Weight (kg)
1619R	VITON (red)	0,4	222 x 65	0,122
1633R		1	280 x 80	0,183
1619J	EPDM (yellow)	0,4	222 x 65	0,122
1633J		1	280 x 80	0,183

RANGE K



DUAL-PURPOSE CONTAINER

COMPLIANCE

UN approved.

ADVANTAGES

- Very robust construction.
- Integrated grip handle.

TECHNICAL FEATURES

- Double wall construction:
 - Metal outer wall coated with blue epoxy paint (RAL 5010) for better protection against impact and fire.
 - Watertight inner wall made of polyethylene and resistant to chemical attack.
- Polyethylene closing cap with 2» threaded joint.
- Capacity: 12 litres.

OPTION

All stainless steel funnel (2" thread) with a flame arrester grid.

51000 ▶

51061B ▶



P/N	Description	Dimensions H x Ø (mm)	Weight (kg)
51061B	Can RAL 5010	345 x 240	1,8
51000	Stainless steel funnel	125 x 140 ⁽¹⁾	0,7

(1) Total height (container + funnel): 530mm.