any time without notice and without incurring obligations.

RANGE 4) FM - NFPA - OSHA







◆ B22S

CONFORMITY

- In compliance with NFPA (National Fire Protection Association). OSHA (Occupational Safety and Head Administration), UL (Underwriters Laboratories) and FM (Factory Mutual international) specifications.

ADVANTAGES

- Sturdy construction for use in industry.
- Integrated self-latching handle.
- Continuous piano hinge provides smooth closure.
- Various models available.

PASSIVE SECURITY

- Built in double wall steel with 38 mm of insulating air space.
- Blue epoxy paint.
- Adjustable galvanized spillslope safety steel shelves with high density polyethylene (HDPE) shelves trays.

- Liquid tight containment sump holds leaks on the bottom (50mm heigh).
- Static ground connection.
- B24M and B24S models euipped with extra polywork tray.

ACTIVE SECURITY

- High and low vent (Ø 50mm) with grid.
- Continuous piano hinge.
- Self-closing⁽²⁾ or manual doors.
- 3 points stainless steel bullet latching system.
- Doors with key-locking system.

OPTIONS

- Additional shelves.
- Industrial absorbent mats for retention tank (10 pieces by pack P/NJF10D).
- Ventilation or filtration boxes.

P/N	Closing doors	Outside dim. H x W x D (mm)	Inside dim. H x W x D (mm)	Storage capacity (L)	Containment capacity (L)	Number of shelves	HDPE protections	Maximum load by shelf(3) (kg)	W. (kg)
B04M	Manual	610 x 430 x 460	465 x 345 x 360	15	6	1	2	159	30
B04S	Slef-closing								32
B18M	Manual	610 x 1090 x 460	515 x 1005 x 390	64	20	1	2	159	75
B18S	Slef-closing								78
ESP18	-	Additional shelf for 64 litres cabinet							4
B22M	Manual	1650 x 585 x 460	1560 x 500 x 390	86	10	3	4	159	90
B22S	Slef-closing								92
ESP22	-	Additional shelf for 86 litres cabinet							4
B24M	Manual	910 x 890 x 560	710 x 795 x 455	90	18	1	2	159	92
B24S	Slef-closing								95
ESP24	-	Additional shelf for 90 litres cabinet							4
B30M	Manual	1120 x 1090 x 460	1025 x 1005 x 390	113	20	1	2	159	105
B30S	Slef-closing								108
ESP30	-	Additional shelf for 113 litres cabinet							5
B45M	Manual	1650 x 1090 x 460	1560 x 1005 x 390	170	20	2	3	159	140
B45S	Slef-closing								143
ESP45	-	Additional shelf for 170 litres cabinet							5
B60M	Manual	1650 x 860 x 860	1560 x 770 x 780	228	30	2	3	159	170
B60S	Slef-closing								173
ESP60	-	Additional shelf for 228 litres cabinet							9

⁽¹⁾These cabinets are not designed for high corrosive products (nitric acid, sulfuric acid, phenol, hydrochloric) and require an exhausting system to improve their life cycle. For the high corrosive products please refer to our Ranges 8.A and 10. For the exhausting system refer our V Range.

⁽²⁾ According to models ⁽³⁾ Evenly distributed